INFORMATION FOR THE INSTALLATION OF HOT WATER HEATERS & PERMITS

CUSTOMERS NAME		PHONE #
LOTAND BLOCK_	NUMBERS THE INFORM	ATION CAN BE FOUND ON THEIR TAX FORMS
TO WHAT MUNICIPALITY, TWP, CITY OR BORO DOES THE CUSTOMER PAY HIS TAXES?		
IS THERE A CARBON MONOXIDE ALARM	VACUUM RELIEF VALVE REQUIRED BY SOME	ELECTRICAL DISCONNECT
YESNO	LOCAL CODES	REQUIRED FOR ALL ELECTRIC HWHS BY CODE, IF ELECTRICAL PANEL IS NOT WITH IN SIGHT OF HWH
*	WATER PRESSURE GAUGE	IS THERE A DISCONNECT YESNO
PRESSURE REDUCING VALVE	MAIN WATER SHUT OFF	SIZE OF WIRE WIRE SIZE ACCORDING TO CODE IS A 10-2 WIRE WITH A 30 AMP BREAKER.
(USED WHERE INCOMING WATER PRESSURE EXCEED 80 PSI) REQUIRED BY LOCA CODES	310	BONDING WIRE ALL HWH'S NEED A BONDING WIRE TO
THERMAL EXPANSION TANK REQUIRED BY MANY LOCAL CODE MEET CODE. YESNO		
REL	LIEF VALVE -	
RELIEF VAL'	EG 6" OFF FLOOR?	CONTROL PANELS
DATA PLATE WHERE THE INFOR	RMATION	THERMOSTATES AND ELEMENTS ARE LOCATED UNDER THESE PLATES UNDER THESE PLATES
ABOUT YOUR HWH HWH DRAIN		
(REQUIRED BY MAI		
ELECTRIC110 V	OLT220 VOLT	
HEIGHT OF EXISTING HWHWIDTHGALLONAGE		
LOCATION OF HWH GAI	RAGECRAWL SPACE	CEBASEMENT
CLOSETFIRST	FLOORSECOND FL	OOR